Solis

THE TOUGHEST PERFORMER FOR YOUR FIELD

H26



- 3 CYLINDER DIESEL ENGINE
- SEPARATE PEDAL FOR FORWARD & REVERSE
- HEAVY DUTY FRONT AXLE
- HYDRAULIC LIFTING CAPACITY 775 KG
- HIGH LOADER LIFTING CAPACITY 640 KG

UPGRADED FEATURES

C Type Charger	Higher LPM pump	Hydraulics Top Link	3DA	FOPS with Canopy
OPG (Operator Protective Guards)	Grill Guard	Foldable PTO Guard	Mid ROPS	Additional Bigger Tyres

FEATURES	H 26
ENGINE	
Engine Type	3-Cylinder Diesel Engine
HP Category	26
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	1319
Rated RPM (+/-25mm)	2500
Air Cleaner	Dry with clogging sensor
Cold Start	Standard
Max Torque (Nm)	76.3
Exhaust	Silencer in the engine compartment, downward discharge
TRANSMISSION	
Drive	4WD
Clutch	Wet type clutch for PTO
Gearbox	Hydrostatic
Front Axle	4WD
Transmission	HST (Hydrostat)
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	21.03@2660
Minimum Speed (Km/Hr)	3.18 at low idle 900 erpm, 8.83@rated erpm
BRAKES	
Brakes	Oil Immersed
Type of Actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK	
Differential Lock	Yes, Foot Operated
PTO	
PTO (rpm)	Mid PTO- 2100 RPM, Rear 540
PTO (actuation)	Electro hydraulic operated/mechanical selector lever
STEERING	
Steering	Power steering
ELECTRICAL	
Battery	12V, 65 Ah
Alternator	12V, 42 A
Seven Pin Trailer Socket	Standard
HYDRAULICS	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Hydraulic Lifting Capacity (Kg)	775
Lift Rods	Standard
Litre Per Minute (LPM)	20
High Loader Lifting Capacity (Kg)	640
SAFETY SWITCH	
PTO Safety Switch	Standard
Neutral Safety Switch	Standard
Clutch Safety Switch	Standard

FEATURES	H 26
CAPACITY (LTRS)(+/-5%)	
Fuel Tank (Lit)	22
TURNING RADIUS	
Without brakes (m) as per standard tyres	3.05 (RHS), 2.62 (LHS)
TYRE	
Front	6.00-12
Rear	8.30-20
DIMENSION & WEIGHT(+/-5%)	
Weight (Kg)	1235
Wheel Base (mm)	1570
Total Length (mm)	2895
Total Width (mm)	1215 (max)-1050 (min)
Height (mm) Up to ROPS	2325
Min Ground Clearance (mm)	240
Front Track (mm)	885
Rear Track (mm)	960
OTHERS	
Fuel Indicator Gauge	Standard
Front Tow Hook	Standard
Front & Rear Weights with std. Ballast	Front weights - 2 x 15 Kg
Trailer Hitch	1. E-marked swinging drawbar 2. Clevis Hitch 3. Semi-Automatic hitch
ROPS	Yes
C - Type Charger	Yes
FOPS	Yes
OPG (with loader)	Optional
Hydraulics Top Link	Standard
Additional Hydraulic Circuit	3DA
USB Charger	Yes
PC/DC	Yes
Wireless Charger	Yes
ROPS Lights	Yes
Bluetooth Speaker	Yes
Mid ROPS	Yes
OPTIONAL FEATURES	
Cabin Option	Yes

TYRES

			
Radial Agri: Front | Rear 6.5/80-12 280/70 R18	Turf: Front | Rear 25x8,50-14 13.60-16	Ind: Front | Rear 23x8,50-12 33x15,50-16,5	Galaxy Pro Front 220/55R12 Rear 280/70R16
Front Loader		YES optional	

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

Solis

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221
Fax:+91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com