Solis

THE TOUGHEST PERFORMER
FOR YOUR FIELD

S 26+









- RELIABLE MECHANICAL TRACTOR
- 3 CYLINDER DIESEL ENGINE
- TWIN PROJECTOR HEADLAMPS
- AGRI/IND./TURF TYRE OPTION
- REINFORCED SAFETY FEATURES



CELEBRATING 1,800,000 TRACTORS GLOBALLY

COST EFFICIENT MECHANICAL TRACTORS

MADE OF REAL STEEL

STRATEGIC COLLABORATION WITH YANMAR

THE TOUGHEST PERFORMER FOR YOUR FIELD

S 26+

Solis



FEATURES	S 26+
ENGINE	
Engine Type	3 Cylinder Diesel Engine
HP Category	26
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	1319
Rated RPM (+/-25mm)	2500
Air Cleaner	Dry with Clogging Sensor
Cold Start	Standard
Max Torque (Nm)	76.3
Exhaust	Silencer in the Engine Compartment, Downward Discharge
TRANSMISSION	
Drive	4 WD
Clutch	Single Clutch
Gearbox	6 Forward + 2 Reverse
Front Axle	4WD
Transmission	Sliding Mesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	16.2@2815 Fly Up
Minimum Speed (Km/Hr)	1.64@2500 rated
BRAKES	
Brakes	Oil Bath Brake
Type of Actuation	Mechanical
Parking Brake	Independent
Differential Lock	
Differential Lock	Yes, Foot Operated
PTO	
PTO (rpm)	540, 1000
PTO (actuation)	Mechanical
STEERING	
Steering	Power Steering
ELECTRICAL	
Battery	12V, 65 Ah
Alternator	12V, 42 A
Seven Pin Trailer Socket	Standard
HYDRAULICS	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Additional Hydraulic Circuit	1DA
Hydraulic Lifting Capacity (Kg)	750
Lift Rods	Standard
Litre per Minute (LPM)	13.5

FEATURES	S 26+
SAFETY SWITCH	
PTO Safety	Standard
Neutral Safety Switch	Standard
Clutch Safety Switch	Standard
CAPACITY (LTRS)(+/-5%)	
Fuel Tank (Lit)	28
TURNING RADIUS	
Without Brakes (m) as per Standard Tyres	3.18 (RHS), 3.10 (LHS)
TYRE	
Front	6.00-12
Rear	8.30-20
DIMENSION & WEIGHT(+/-5%)	
Weight (Kg)	1070, 1265 with Cabin
Wheel Base (mm)	1560
Total Length (mm)	2760
Total Width (mm)	1075 (max) - 1055 (min)
Height (mm) Up to ROPS	1955
Min Ground Clearance (mm)	240
Front Track (mm)	885
Rear Track (mm)	835
OTHERS	
Fuel Indicator Gauge	Standard
Front Tow Hook	Standard
Front & Rear Weights with std. Ballast	Front weights - 2 x 15 Kg
Trailer Hitch	Drawbar / Optional Towbar
ROPS	Yes
OPTIONAL FEATURES	
Cabin Option	Yes

Tyres

 Radial Agri: Front I Rear	 Turf: Front I Rear	 Ind: Front I Rear	 Galaxy Pro: Front I Rear
6.5/80-12 280/70 R18	23x8.50-12 33x15.5-16.5	23x8.50-12 33x15.5-16.5	220/55R12 280/70R16
Front Loader		YES optional	

DEALER STAMP

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221
Fax:+91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com